BTLIC.R25044 Plastic Materials

Page Bottom

Plastic Materials

See General Information for Plastic Materials

HOME INSULATION CORP R25044

967 EDGELEY BLVD CONCORD, ON L4K 5Z4 CANADA

Classified as to surface burning characteristics in accordance with CAN/ULC-S102.

	Classification or Rating	
Material Details	Flame Spread	Smoke Developed
Finished foamed plastic formed from formed from isocyanate component Insulthane 100 A and resin component Insulthane 100 B, 6.9 kg/m^3 maximum density, 140 mm maximum thickness	395 - 455	330
Finished foamed plastic formed from formed from isocyanate component HOME FOAM A and resin component HOME FOAM B, 6.9 kg/m³ maximum density, 140 mm maximum thickness	395 - 455	330

Last Updated on 2006-07-25

<u>Questions?</u> <u>Notice of Disclaimer</u> <u>Page Top</u>

Copyright © 2009 Underwriters' Laboratories of Canada®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under ULC's Follow-Up Service. Only those products bearing the ULC Mark should be considered to be Listed and covered under ULC's Follow-Up Service. Always look for the Mark on the product.

ULC permits the reproduction of the material contained in the Online Certifications Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories of Canada" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories of Canada®"

An independent organization working for a safer world with integrity, precision and knowledge.

